

AD68N-0100

Cabo Detecção Linear Digital Alarmline II - 68°C, Revestimento Nylon, 100m

General

The AD68N-0100 is a Digital Linear Heat Detection (LHD) cable with a 68°C (155°F) fixed temperature activation rating. It has a Nylon outer sheath for UV protection and increased durability for external applications and is supplied in 100m lengths.

The AD range of digital sensor cables provides a very simple fixed temperature heat detection system which can be used in many applications where other forms of detection are not suitable.

Operation

The AD range of digital LHD cables contains a pair of twisted, low resistance, tri-metallic conductors sheathed with advanced temperature sensitive polymers. The cable operates by softening the insulation of the conductors, the tension of the twisted conductors then causes the two cores to fuse together. The sensor cable provides a simple switch operation which when used with a combination of end-of-line (EOL) monitoring and alarm trigger resistors can signal an alarm to any fire monitoring equipment through any monitored input i.e. conventional detection zone or addressable interface unit.

Location Control Unit

Additional to the LHD sensor cable, an optional digital location control unit which monitors the sensor cable and can identify along the length of the sensor cable where an alarm condition has occurred, is also available.

Cable fixings for all applications

A range of 'edge', 'A', 'P', and 'T' clips allow the cable to be properly installed. The clips provide heat insulation as well as holding the cable at the correct distance from cable trays, steel works, ceilings and walls.



Detalhes

- cUL/UL 521 approved
- Up to 3000m (10,000ft per zone)
- Detection along total cable length
- Optional extrusions for different environments
- Simple maintenance free installation
- Suitable for use in hazardous areas
- RoHS Compliant

AD68N-0100

Cabo Detecção Linear Digital Alarmline II - 68°C, Revestimento Nylon, 100m

Especificações técnicas

Elétrica

Tensão de operação 0 to 30 VAC, 0 to 42 VDC

Nr. de condutores 2

Condutor

Resistência ~100 ohms/km per leg (30.4 ohms/Kft)

Capacitância 88 to 150 pF/m

Indutância 540 to 1050 nH/m

Físico

Dimensões físicas 4.44 mm ±0.12 mm (nominal outside diameter)

Peso líquido 2.52 kg

Cor Preto

Tipo de montagem Fixação por cabo

Ambiental

Temperatura de operação 45°C (113°F)

Humidade relativa 0 to 100% noncondensing

Ambiente Interior, Exterior

Regulamentação

Certificação CE, UL



Como empresa de inovação, a Carrier Fire & Security reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 14 February 2024 - 16:39