

AI2672

Sinalizador de Loop - Série 2000

General

The AI2672 is a 2000 series, addressable remote indicator. It is used to repeat an alarm condition signalled from one or more devices for which the alarm LEDs on the devices may be obscured or not visible in plain sight. The AI2672 is fully programmable when using a fire panel (CIE) supporting 2000 series addressable protocol.

Addressable and Loop Powered

The addressing on the AI2672 is done via easy to use, DIP switches, and allows the device to be programmed similar to other notification devices on the 2000 series loop. It can be freely controlled from the CIE and simply be assigned to duplicate the required detector (or other device) status.

Installation

The AI2672 is housed in a plastic enclosure suitable for surface mount assembly on commercial switch boxes. Two 10 mm LEDs are installed on either side of the body of the device to ensure clear visibility in all directions, allowing the AI2672 to be used for both ceiling mount as well as wall mount applications.



Detalhes

- Wide operating voltage
- Low current consumption
- Wall or ceiling mounted
- Low profile
- 360°, clearly visible, large LEDs

AI2672

Sinalizador de Loop - Série 2000

Especificações técnicas

Elétrica

Tensão de operação	20 to 30 VDC
Consumo de corrente	0.3 mA (Quiescent) 2.3 mA (Alarm)

Físico

Dimensões físicas	85 x 29 x 85 mm (W x H x L)
Peso líquido	65 g
Cor	Branco

Ambiental

Temperatura de operação	-10 to +50°C
Ambiente	Interior
Classificação IP	IP50

Regulamentação

Certificação	CE
--------------	----



Como empresa de inovação, a Carrier Fire & Security reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 25 September 2024 - 11:48