

AS2364W

Sirene Interior de Loop Branca Base Funda- Série 2000

General

The AS2364W is a WHITE bodied, deep base addressable room sounder for fire alarm systems running 2000 series addressable fire protocol. Multiple tone selection and full CPD approval ensure conformance to local regulations.

The sounders operate over a 2-wire 2000 series loop and are loop powered i.e. no external power supply is required. They are compatible with automatic phased-start synchronisation controlled from the fire panel. The AS2364W has a IP65 enclosure.

Installation

Device cabling is done to the base and allows the sounder to be fitted and locked into position afterwards. A separate earth terminal is provided in the base for connecting the screen or functional earth when required.

Efficient and versatile

These sounders can be put into different operating modes depending on local requirements. It provides high sound output at a low current, thus reducing power standby requirements and overall system cost. They are supplied with high/low volume settings as standard, allowing final audio adjustments to be made during installation.

The sounder is tone selectable during installation. 32 tone settings are available.



Detalhes

- Loop powered
- High sound output with low current consumption
- Multiple tone selection
- Suitable for multiple stage evacuation with up to 3 pre-set tones
- Automatic synchronisation
- IP65 rated
- CPD certified

AS2364W

Sirene Interior de Loop Branca Base Funda- Série 2000

Especificações técnicas

Elétrica

Tensão de operação	17 to 28 VDC
Consumo de corrente	5.1 mA @ 24 V (Sounder activated) <1.2 mA @ 24 V (Switch on surge) 310 µA @ 24 V (Quiescent)

Sirene

Nível de saída	97 dBA at 1m (Output @ 90° ± 3 dB(A)) (depends on selected tone and input voltage)
Ajuste nível de saída	8 dB
Frequência	400 to 2850 Hz (depends on selected tone and input voltage)
Tons selecionáveis	32

Físico

Dimensões físicas	100 x 104 mm (Ø x H)
Peso líquido	250 g
Material	Alto impacto policarbonato

Ambiental

Temperatura de operação	-10 to +55°C
Temperatura de armazenamento	-10 to +55°C
Humidade relativa	5 to 95% noncondensing
Ambiente	Interior
Classificação IP	IP65

Regulamentação

Certificação	EN54-3
--------------	--------

Physical

Cable size	0.28 to 2.5 mm ²
------------	-----------------------------

Produtos compatíveis

Categoria	Referência	Descrição
Dispositivo notificação	AS36RIM	Anel de Remate para Sirene, com Texto "FIRE"
Dispositivo notificação	AS36RIM-09	



Como empresa de inovação, a Carrier Fire & Security reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 25 September 2024 - 11:48