

## AS273 Indoor siren, 2 tones - with flash



## **Details**

- Low current consumption
- 2 tone
- Flash light
- Pry-off & opening tamper protection
- Easy to install (1 fixing screw for cover)
- Vertically or horizontally mounting
- Self activating version available
- ANPI, NFA2P and VdS version available

## $\begin{array}{l} AS273 \\ \text{Indoor siren, 2 tones - with flash} \end{array}$

## **Technical specifications**

_	
General	
Accessory group	Siren
Туре	Indoor siren
Sounder output (dB @	101 dB at 1 m (typical)
distance)	
Flash specifications	
Current consumption	110 mA
Light output	100,000 peak lumens
Flash frequency	60 flashes/minute
Electrical	
Power supply value	10.0 to 14.2 VDC
Operating voltage	10 to 14.2 V
Current consumption	120 mA at 12 VDC (typical)
Physical	
Physical dimensions	155 x 114 x 44 mm
Net weight	249 g
Colour	White
Material	ABS
Environmental	
Operating temperature	-25 to +55°C
IP rating	IP315
Regulatory	
Certification	CE



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.