

AS363W

Sirene Branca, Seleção de Toque e Base Baixo Perfil - Convencional

General

The AS363W is a general purpose electronic sounder for fire alarm applications. Which features a special base containing all wiring connections and allow for easy removal/placement of the sounder.

Easy and Fast Installation

The AS363W alarm sounder allows faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws, these sounders use TimeSaver™ bases from the 630 series detectors. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

Efficient and versatile

The AS363W provide high sound output at a low current, thus reducing power requirements and system cost. The AS363W sounder is supplied with a volume control as standard, allowing final audio adjustments to be made during installation.

With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation. A second tone, is available if extra wires are installed in the sounder circuit.

The mechanism for locking the sounder to the base, can be activated if required. Once activated, a special tool is required to remove the sounder from the base.



Detalhes

- High sound output
- Low current consumption
- 32 Tones user selectable
- Automatic synchronisation
- Volume control
- Anti-Tamper locking mechanism
- Shallow mouting base
- Wiring directly to base
- Two stage alarm
- VdS Approved

AS363W

Sirene Branca, Seleção de Toque e Base Baixo Perfil - Convencional

Especificações técnicas

Geral

Monitorização de linha polarised input

Elétrica

Tensão de operação 17 - 60 VDC (EN54-3 / fire applications)
9 - 60 VDC (non-fire applications)

Consumo de corrente 4 - 41mA @ 24 VDC (see tone table in manual)

Sirene

Nível de saída Sound output at 1 m (see tone table in manual):
94 to 106dB(A)

Tons selecionáveis 32

Sincronização Phased start (automatic)

Físico

Dimensões físicas 100 x 81 mm (Ø x D)

Peso líquido 215 g

Cor Branco

Material Alto impacto policarbonato

Ambiental

Temperatura de operação -25 to +70°C

Ambiente Interior

Classificação IP IP21

Regulamentação

Certificação EN54-3



Como empresa de inovação, a Carrier Fire & Security reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 27 September 2024 - 11:16