#### **Product data sheet**



# AS506

## Self-activating outdoor siren with single red beacon



#### **Details**

- · Attractive high quality shaped housing
- $\bullet\,$  Double piezo sounder with 114 dB @ 1m sound output
- · Vertical or horizontal mounting
- Fully potted electronics
- On-board Ni-Cd-battery
- Strobe flash light
- Selectable comfort LED indication
- Pry-off and opening tamper detection
- Self detection of cable cutting or tampering
- Installer friendly
- Hold-off polarity selection
- Independently hold-off for both beacon and siren
- A choice of cut off time
- Selectable tamper configuration

## AS506

## Self-activating outdoor siren with single red beacon

## **Technical specifications**

General		
	Siren	
Accessory group Type	Outdoor siren	
Туре	Outdoor sirem	
Electrical		
Operating voltage	10 to 14.5 V	
Current consumption	350 mA	
Physical		
Physical dimensions	210 x 300 x 55 mm	
Net weight	1011 g	
Environmental		
Operating temperature	-25 to 55 °C	
Material		
	Polycarbonate (3 mm)	
Sounder		
	Double piezo	
PCB protection		
	Fully potted	
Tamper & pry-off		
	Yes	
Power supply		
	10.0 to 14.5 VDC	
Standby current (typical)		
	40 mA (with NiCd battery)	
	20 mA (without battery)	
Operating current (	(typical)	
	350 mA	
Sound output		
	114 dB	
Frequency		
	0.5 to 3 kHz	
Operating temperature		
, 5	-25 to +55°C	
Flash frequency		
- Idon noquonoy	50 to 60 flashes/min	
Cut-off timer		
	3 min, 5 min, 10 min, 20 min	
Comfort LED		
	Yes	
Dimensions (W x H x D)		
Dillicipatoria (W X II	210 x 300 x 55 mm	

Low voltage detection	
	Yes
Metal inner cover	
	Optional
On-board self-activ	vating battery
	10.8 V / 280 mAh

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

