

AS527

Sirene Exterior Autoalimentada 2 Lentes Âmbar - 114 dB

The AS520 Series comprises a range of quality designed sirens that meet today's security and environmental residential requirements. With its attractive housing, the choice of lens colours and the possibility to mount horizontally or vertically the siren can easily fit any place. The housing in UV-proof and high impact resistant, 3-mm polycarbonate and an optional inner cover provide the ultimate protection.



Detalhes

- Attractive high quality shaped housing
- Double piezo sounder with 114 dB @ 1m sound output
- Vertical or horizontal mounting
- Fully potted electronics
- Double strobe flash light
- Selectable comfort LED indication
- Pry-off and opening tamper detection
- Self detection of cable cutting or tampering
- Hold-off polarity selection
- Independently hold-off for both beacon and siren
- A choice of cut off time

AS527

Sirene Exterior Autoalimentada 2 Lentes Âmbar - 114 dB

Especificações técnicas

Geral

| | |
|----------------------------------|-------------------------|
| Grupo de acessórios | Sirene |
| Tipo | Sirene exterior |
| Saída da sirene (dB @ distância) | 114 dB at 1 m (typical) |

Especificações do flash

| | |
|---------------------|----------------------|
| Frequência de Flash | 50 to 60 flashes/min |
|---------------------|----------------------|

Elétrico

| | |
|---------------------|--|
| Tensão de operação | 10 to 14.5 VDC |
| Consumo de corrente | 350 mA 40 mA (standby, with NiCd battery) 20 mA (standby, without battery) |

Físico

| | |
|-------------------|-------------------------------|
| Dimensões físicas | 210 x 300 x 55 mm (W x H x D) |
| Peso líquido | 1053 g |
| Material | Polycarbonato |

Ambiental

| | |
|-------------------------|-------------|
| Temperatura de operação | -25 to 55°C |
| Classificação IP | IP54 |

Physical

| | |
|-------------------|----------------------|
| Material | Polycarbonate (3 mm) |
| Metal inner cover | Optional |

Sounder

| | |
|---------------|------------------|
| | Double piezo |
| Frequency | 0.5 to 3 kHz |
| Cut-off timer | 3, 5, 10, 20 min |

Security

| | |
|------------------|--------------|
| Tamper & pry-off | Yes |
| PCB protection | Fully potted |

Comfort LED

| | |
|--|-----|
| | Yes |
|--|-----|

Battery

| | |
|-------------------------|------------------|
| | Optional |
| Low voltage detection | Yes |
| Self-activating battery | 10.8 V / 280 mAh |



Como empresa de inovação, a Carrier Fire & Security reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 26 April 2024 - 17:09