

ATS1135

Teclado LCD 2x16 Carateres com Leitor - ATSx500

Simplified user interface

The ATS1135 is a new addition to the Advisor Advanced product family, having a simplified end user operation: quick arm functionality, 2 levels of partset, programmable function keys. The existing range of indoor/outdoor keypads and card readers can be used in different environments.

Stylish design

The ATS1135 has a modern stylish design and has a clearly readable text on a large 2 x 16 characters LCD for displaying system programming, alarm and access control functions. The contrast and intensity of the display is adjustable via the keypad as well as the volume level of the built-in buzzer. Four arrow keys will navigate the user easily through the programming and operational features and 4 additional fixed functions keys will complete this user-friendly interface next to the 3 programmable function keys A,B &C.

Built-in card reader

The ATS1135 has a built in smart card reader. The ATS1135 can be used for arming/disarming using either the PIN or the card or a combination of the two for higher security needs. It is suitable for using the multiple card badging techniques which are available for the Advisor Advanced product family. A user can set the system in the evenings by badging his card three times within 10 seconds interval. Another application could be for doors which can be programmed so that badging once unlocks the door to allow people in and out without card, and badging three times re-locks the door.

LED Indication

Four status LED's will continuously update the user on mains condition, faults, access control and alarms.

Green - Power LED is on when the control panel is powered by the AC supply.

Yellow - Fault LED illuminates to indicate detection of a system fault. Blue - Access LED flashes when access to an area assigned to the RAS is granted.

Red - Alarm LED illuminates when there is a system tamper or an area assigned to the RAS is in alarm state.

The Arming Station can display the status of an area or complete system via the status indication LED in between the navigation keys. When Green the area or system is disarmed, when Red the system is an armed or part armed state.

Mounting

The ATS1135 can be mounted by using the mounting points in the backplate which also provides easy cable entry to connect the panel to the removable bus connector.

A backplate (ATS1135BPL) is available which can be used to cover the dimensions of a legacy keypad when updating an installation to the Advisor Advanced system.



Detalhes

- Simplified end user operation
- Large 2 x 16 characters LCD
- · Compatible with Axon and Advisor Advanced panels
- User adjustable LCD contrast
- User adjustable buzzer
- · Built-in smart card proximity reader
- Compatible with all Advisor Advanced control panels
- Clear system status indication
- 3 programmable function keys

ATS1135

Teclado LCD 2x16 Carateres com Leitor - ATSx500

Especificações técnicas

Geral	
Interface utilizador	2 x 16 Char LCD, Teclas
Linha de produto	Advisor Advanced
LEDS de Estados	2
Leitor integrado	Proximidade
Sistema	
Teclas de Função	3
Tipos de cartão suportados	HiTag2
Tipo de endereçamento	DIP Switches
Tipo de cabo suportado	WCAT 52/54 or equivalent
Comunicação	
Tipo de Comunicação	Fio
Distância de leitura	5 cm
Entradas / saídas	
Entradas	1
Tipo de entrada	Request to Exit
Saídas	1
Tipo de saída	Open collector, 15 V max. at 50 mA max.
Elétrica	
Tensão de operação	8.5 to 14 VDC
Consumo de corrente	35 mA normal operation 155 mA max.
Físico	
Dimensões físicas	200 x 90 x 24 mm
Net weight	350 g
Cor	Branco
Fator de forma	Horizontal
Tipo de montagem	Montagem em superfície
Ambiental	
Temperatura de operação	-10 to +55°C
Humidade relativa	0 to 95% noncondensing
Ambiente	Interior
Classificação IP	IP30
Regulamentação	
Grau EN50131	Grau 3
Conformidade	CE, RoHS
Certificação	VdS



Como empresa de inovação, a Carrier Fire & Security reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.