### **HD PRO**

Series marked for the installer looking for a high-level camera emphasizing the difference in image quality. The Pro series cameras are suitable for indoor and outdoor applications where professional video surveillance is required.



PROVISION IS

## **DI-320A-28**

#### 20m IR 2MP Fixed Lens Small Dome/Turret Camera

Equipped with a 2.8mm fixed lens, this 2MP dome/turret camera is designed for short distance surveillance systems (up to 20m) for both indoor and outdoor scenarios. Featuring 4in1 technology selectable by a protected dipswitch the camera is ideal for Plug & Play over existing analog infrastructure.























## **MAIN FEATURES**

- DI-320A-28 20m IR 2MP Fixed Lens Small Dome/Turret Camera
- Sensor: 1/2.9" 2MP CMOS Sensor
- Selectable Output: 2MP: 1920×1080 AHD/TVI/CVI 1MP: 1280×720 AHD/TVI/CVI CVBS: 700TVL
- Lens: 2.8mm Mega-Pixel Fixed (88°)
- True Day&Night-ICR

- 3D-DNR/HLC/BLC
- Illumination: 20m (1 High-Power IR LED)
- IP67
- Weight: 490g
- Power: DC12V/300mA



https://provision-isr.com



## **SPECIFICATIONS**

Video		
Image Sensor	1/2.9" 2MP CMOS Sensor	
Image Format	16:9	
Effective Pixels	1936x1096	
Scanning System	Progressive	
Min. Illumination	Color: 0.005lux@F1.2, AGC ON B/W: 0lux with IR	
Day & Night	True Day&Night-ICR	
Day & Night Modes	Ext/Auto/Day/Night	
Compression		
Resolution	2MP: 1920x1080 AHD/TVI/CVI 1MP: 1280x720 AHD/TVI/CVI CVBS: 700TVL	
Frame Rate	25/30FPS	
Image		
Backlight Compensation	No	
S/N Ratio	≥52dB (AGC OFF)	
Privacy Zone	no	
Noise Reduction	3D-DNR	
Image Enhancement	BLC, HLC	
On Screen Data		
CoC Support	Yes	
OSD Menu	Available via CoC Only	
Lens		
Field of View	2.8mm Mega-Pixel Fixed (88°)	
Iris	Fixed Iris	
Lens Mount	M12 Mount	

# **DI-320A-28**



Connectivity	
Video Output	2MP / 1MP (Selected by OSD Menu) AHD/TVI/CVI/CVBS + PAL/NTSC (Selected by DIP Switch)
Audio Connectivity	N/A

Housing	
Illumination	20m (1 High-Power IR LED)
Bracket	3-Axis Bracket
Protection Rate	IP67
Dimensions	Ф97*82.6mm
Weight (gross)	490g
Power	DC12V/300mA
Work Environment	-30°C ~ 50°C , 10% ~ 90% humidity



# **DIMENSIONS**

