

## General

---

The DM700KY-N is a high quality, yellow plastic manual call point with key switch.

The key switch has 2 positions, with the key being trapped in one position and removable in the other. Changing between these positions require the turn of the key through a 90° angle. It offers three electrical connections, which already come fitted with flying leads. One of these connections are common, while the tuning of the key result in the change over between the other two.

## Construction

---

The robust switching device comprises a main housing and escutcheon plate. It is fitted to the plate which simply snaps into the main housing and is permanently located in place with fixing screws. All units are supplied with 2 sturdy keys.

## Standard Features

---

- Easy to install
- High quality key switch
- Operates after long period of disuse
- Preformed mounting slots
- Surface mount

## Specifications

### Electrical (switch specifications)

Maximum voltage	250 Vac
Maximum current	2A @ 250 Vac
	4A @ 125 Vac
	4A @ 28 Vdc

### Environmental

Operating temperature	-20°C to +55°C
Relative humidity	0 to 90% RH (non-condensing)
IP Rating	IP21

### Mechanical

Size	87mm (W) x 87mm (H) x 52mm (D)
Weight	166 g
Color	Yellow
Functional marking	"EXTINGUISHANT ABORT"

## Ordering Information

Part No.	Description
DM700KY-N	Manual call point Yellow, 2-position keyswitch, surface mount
DMN782	Hinged transparent MCP protection cover