



# KMD300

## 300 Series Carbon Monoxide (CO) Detector and Base



### Details

---

- Complies with UNE 23300:1984, CE, WEEE, RoHS
- Microprocessor based, SMT technology
- Electrochemical CO sensor with high gas discrimination
- Resolution of up to 1 ppm, less than 5% error in measurement
- Fast response time
- No calibration required
- Low current consumption
- BI-Colour diagnostic LED
- Supported by KM300 CO panels
- Useful life of 5 years
- Number of detectors per zone

# KMD300

## 300 Series Carbon Monoxide (CO) Detector and Base

### Technical specifications

---

#### Electrical

Operating voltage	10 to 20 VDC (supply voltage)
Current consumption	6 mA (quiescent current) 15 mA (alarm current)

---

#### Detection

Detection principle	Electrochemical
Coverage area	300 m <sup>2</sup> max.
Range	0 to 300 ppm

---

#### Physical

Physical dimensions	124 x 62 mm (Ø x H, including base)
Net weight	0.3 kg

---

#### Environmental

Operating temperature	-10 to +40°C
Storage temperature	-10 to +70°C
Relative humidity	10 to 95%
IP rating	IP42

---

#### Compatible products

Category	Reference	Description
Detection device	KZD705	
Panel	KM301	Carbon Monoxide Control Panel for Car Parks - 1 Zone
Panel	KM302	
Panel	KM303	
Panel	KM304	

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [za.firesecurityproducts.com](http://za.firesecurityproducts.com) online or contact your sales representative.

Last updated on 13 February 2024 - 12:14