



## **VALKYRIE VOX A**

## ADDRESSABLE VOICE SOUNDER



The VALKYRIE VOX A is a wall mounted Addressable Voice Sounder which is available in either red or white housings. The VALKYRIE VOX A voice sounder is based on our successful Horn type sounder and sounder/ beacon. Up to 32 individually addressed sounders can be installed per loop occupying an address in the range 94 to 125, it can be also configured the shadow mode. The address is set using switches 1 to 5 of the 8 way DIL switch.

With message selection directly programmable via the standard sounder programming of GFE fire alarm control panels, the VALKYRIE VOX A, can broadcast up to 5 differentiated pre-loaded messages: Alert, Fire, Evacuation, Test and Silence Message. The desired messages can be downloaded from our own proprietary recording PC application (VOX LOADER), via a standard USB interface. This product is Loop Controlled and Loop Powered.

## **KEY FEATURES**

- Multi-Language and Multi-Message. Follows Panel's Sounder Programming
- 107dBA maximum sounder output at 1m
- Messages easily programmed via USB interface using dedicated software (VOX LOADER)
- Synchronization for fast activation

TECHNICAL SPECIFICATIONS

TECHNICAL OF ECH TOATIONS	
SUPPLY VOLTAGE	Loop: 20V to 30V DC
LOOP CURRENT	0.7 mA (Quiescent) - 7.5 mA Max. (Sounder active or charging)
LOOP CURRENT - ALARM BEACON	1.4 mA
SOUNDER OUTPUT @ 1 METER	Tone 104 dBA - Voice Message 107 dBA
MAX. CABLE SIZE	2.5 mm²
OPERATING TEMPERATURE	-10°C to 55°C
MAX. HUMIDITY	95% RH Non-Condensing
COLOUR / CASE MATERIAL	Red or White / ABS and PC
PROTECTION CATEGORY	IP21C - Type A - Indoor use
DIMENSIONS / WEIGHT	110 (D) x 85.1 (A) mm / 270g - 325g included mounting base

## ORDER CODE

VALKYRIE VOX A	ADDRESSABLE VOICE SOUNDER
VALKYRIE VOX AB	ADDRESSABLE VOICE SOUNDER WITH BEACON





